


Charlotte plaatvaip:



Product definition		: cut pile
Gauge		: 1/8"
Pile fibre		: 100% polyamide (SDN)
Pile weight		: 1175 g/m ² ± 5%
Pile height	ISO 1766	: 4,3 mm ± 5%
Primary backing		: PA/PES non-woven - Colback
Tile backing		: Polyflex with glass fibre scrim
Total thickness	ISO 1765	: 8.0 mm ± 5%
Total weight		: 4 800 g/m ² ± 7,5%
Tile size		: 50 x 50 cm / 100 x 25 cm / 100 x 50 cm 100 x 100 cm / 100 x 200 cm

PERFORMANCE

Use classification		: Class 32
Castor chair test	EN 985	: pass
Abrasion	EN 1963	: pass
Vettermann test	ISO TR 10361 / EN 1471	: pass
Thermal isolation	ISO 8302	: 0,15 m ² K/W
Dimensional stability	ISO 2551	: pass

ELECTROSTATIC PROPERTIES

Walk on test	EN 1815	: -0,6kV
Static loading		: anti-static

FLAME PROPERTIES

Reaction to fire	EN ISO 11925-2 EN ISO 9239-1	: Bfl - s1
------------------	---------------------------------	------------

COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	: 7-8
Rubbing, dry	ISO 105 X12	: 5.0
Rubbing, wet	ISO 105 X12	: 5.0
Water	ISO 105 E01	: 4-5
Water stains	EN 1307/F	: 4-5

