

MULTICONTRACT

Padova plaatvaip



Product definition		: loop pile
Guage		: 1/10"
Pile fibre		: 100% polyamide
Pile weight		: 650 g/m ² ± 5%
Number of knots	ISO 1763	: 172 000 ± 5%
Pile height	ISO 1766	: 3,0 mm
Primary backing		: PA/PES non-woven
Title backing		: Polyflex with glass fibre scrim
Total thickness	ISO 1765	: 6,0 mm
Total weight	ISO 8543	: 4284 g/m ² ± 5%
Tile size	EN 994	: 50 x 50 cm

PERFORMANCE

Use classification	EN 1307	: Class 33
Castor chair test	EN 985	: pass
Abrasion	EN 1963	: pass
Vettermann test	ISO TR 10361 / EN 1471	: pass
Thermal isolation	ISO 8302	: 0,15 m ² K/W
Dimensional stability	EN 986	: ≤ 0,2 %
Impact sound insulation	ISO 10140	: 26 dB

ELECTROSTATIC PROPERTIES

Walk on test	EN 1815	: ≤ 2 kV
Static loading		: anti-static

FLAME PROPERTIES

Reaction to fire	EN 13501	: Bfl - s1
------------------	----------	------------

COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	: ≥5.0
Rubbing, dry	ISO 105 X12	: 5.0
Rubbing, wet	ISO 105 X12	: 5.0
Water	ISO 105 E01	: 4-5
Water stains	EN 1307/F	: 4-5

